



Configuration

Frame with backrest adjustment

100/125 mm castors with brakes

Custom seat with an opening left/right/front/back/middle or no opening

Backrest with canvas or upholstered and/or side support

Push handles

Armrests in different shapes and heights

Custom upholstered armpads

Height-adjustable, (comfort) legrests with folding footrests

Height-adjustable one-piece footrest

Upholstered footrests

Adjustable headrest

Pelvic belt

Abduction bobbin

Calf strap/calf protector

Insertion rails for bedpan/toiletbucket

Stainless steel bedpan/toiletbucket

Other individual customisation

Application possibilities

- Shower use
- Toilet use (roll-over)
- Hip width 48-54 cm
- Pressure ulcer prevention
- Incontinence prevention
- Reduced torso stability
- Hip angle restriction
- Scoliosis
- Small or large knee angle
- Short or varying leg length
- Small or large ankle angle (equinus foot)
- Amputation
- Differing body measurements
- Stationary use (without castors)
- Tripping propulsion
- Individual customisation

Width wheelchair incl. wheels 65 cm

Seat width 48-50-52-54 cm

Seat height floor – top of the seat 48-69 cm

Length wheelchair ca. 88 cm

Weight wheelchair ca. 17 kg

Loadable weight 150 kg

Recommended distance:
wall to toilet rim From 55 cm

Toiletheight 40-50 cm

These specifications are only an indication and strongly depend on configuration and adjustment.

Scan for the pre-fit form

