



Configuration

Frame with height and backrest adjustment
20/24" Wheels and 100/125 mm front wheels
Rubber slipcover or push rims with tetranops
Knee lever brakes/extended brakes/scissor brakes
Custom seat with an opening left/right/front/back/middle or no opening
Backrest with canvas or upholstered and/or side support
Push handles
Armrests in different shapes and heights
Custom upholstered armpads
Height-adjustable, (comfort) legrests with folding footrests
Height-adjustable one-piece footrest
Upholstered footrests
Anti-tip system
Adjustable headrest
Pelvic belt
Calf strap
Insertion rails for bedpan/toiletbucket
Stainless steel bedpan/toiletbucket
Other individual customisation

Application possibilities

- Shower use
- Toilet use (not roll-over)
- Tripping (propulsion with arms and/or legs)
- Hip width 48-54 cm
- Pressure ulcer prevention
- Incontinence prevention
- Reduced torso stability
- Hip angle restriction
- Amputation
- Differing body measurements
- Individual customisation

Width wheelchair incl. wheels	73-77 cm
-------------------------------	----------

Seat width	48-50-50-54 cm
------------	----------------

Seat height floor – top of the seat	42-51 cm
-------------------------------------	----------

Length wheelchair ca.	79 cm
-----------------------	-------

Weight wheelchair ca.	18 kg
-----------------------	-------

Loadable weight	150 kg
-----------------	--------

Recommended distance: wall to toilet rim	N/A
---	-----

Toiletheight	N/A
--------------	-----

These specifications are only an indication and strongly depend on configuration and adjustment.

Scan for the pre-fit form

